

CLOSED
MAY 2017



The Standard

ENGINE LOG

ASA-SE-1

LOG - #2, 2-DEC-2004
CLOSED 1 MAY - 2017
Charles H. Moore
ASP 1334075



The Standard

ENGINE LOG

ASA-SE-1

The Standard Engine Log
SE-1

© 1993-2000 Aviation Supplies & Academics, Inc.

ISBN 1-56027-416-6

ASA-SE-1

All rights reserved.
Reproduction or use, without
expressed permission, in any manner,
is prohibited.

Published by
Aviation Supplies & Academics, Inc.
7005 132nd Place SE
Newcastle, WA 98059-3153

Printed in U.S.A.



P N R A S A - S E - 1



9 781560 274162

Engine Record General Information

Manufacturer LYCOMING Model O-360-A1F6
Serial L-15677-36A Type Certificate _____
This engine is currently installed in aircraft CESSNA 177-B N34125
CARDINAL
Minimum Octane Fuel 100LL Oil Grade: Summer _____ Winter _____
Magneto Time 25° BTG Point Setting _____ Firing Order _____
Spark Plug Gap .018 TO .022
Manufacturer recommended overhaul at 2000 hours

Registered Owner Record

CELL PH. 1-314-917-3584
PH NO. 1-314-837-2499

Name CHARLES H. & NELLIE MORRIS Address 18 CASTLE DR ZIP 63034

City FLORISSANT State MO From To

Name Address

City State From To

Name Address

City State From To

Name Address

City State From To

Name Address

City State From To

Name Address

City State From To

Notes

YEAR: 2004 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
10/3	186.32			DRAINED ENG. OIL, REMOVED OIL FILTER - OPEN OIL FILTER & INSP- SENT OIL SAMPLE TO BLACKSTONE LAB'S RESULTS ON FILE - OIL REPORT DATED 10/12/04. INSTALLED A NEW CHAMPION CH48103-1 OIL FILTER, TORQUED & SAFETYED. INSTALLED 70TS AERO SHELL 80 GRADE 40WT OIL - ENG. RUN - UP - NO LEAKS. AP Charles H. Morris AP 1334075. END
PAGE 1				

YEAR: 2004 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
10/26	188.29			REMOVED ENG. DR. FUEL PUMP (PRECAUTIONARY) AC P/N 41271 S/N AND INSTALLED O.H. AC P/N 41271 S/N AA18716 USING NEW NYC. GASKET. TORQUED MOUNT BOLTS AND SAFETYED. INSTALLED FUEL LINES & TORQUED FITTINGS. RUN ENG. CK FOR FUEL & OIL LEAKS, NONE NOTED PRESS 4+ PSI. Charles H. Morris AP 1334075. END
PAGE 2				

[illegible]

YEAR: 2004 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
12/2	202.91	TSN	3856.2	ENGINE ANNUAL INSPECTION
		SOH	1326.6	COMPRESSION CHECK
			330.1	CYL'S #1-79/80 #2-78/80 #3-79/80
				#4-79/80
				INSTALLED ALL NEW CHAMPION REM 40-E
				SPARK PLUGS - CK'D MAG-TIMEING 25° BTC
				CHK'D ENG. CONTROLS FOR SECURITY, CONDITION &
				TRAILER'S STOP TO STOP. CHK'D ALL OIL & FUEL
				LINE'S FOR ^{SERVICE} CONDITION & SECURITY & LEAKS.
				WASHED ENG.
				AD 2004-10-14 NOT APPLICABLE SINCE NO
				PROP STRIKES.

PAGE 4

[illegible]

YEAR: 2004	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations
DATE			TSMOH	Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
12/3	20291	54	1,327.0	OIL SAMPLE REPORT - NORMAL ON FILE
		T.T.	3,856.2	UNIT NO. N34125 / REPORT DATE 12/3/04
				LAB NO. C33084 - REF: BLACKSTONE
				LABORATORIES. Entry made by
				Charles H. Mowbray AD 1334075.
				- END -
3/26/05	22276		3897.7	DRAINED ENG. OIL - TOOK OIL SAMPLE SENT
MINUS WHEN CORRECTED	32.67	TOTAL TACH W/OUT SUBSTITUTION		TO BLACKSTONE LABS - REMOVED OIL FILTER - OPENED
	195.17			& FILTER ELEMENT 7252. REVISED 3 SMALL FLAKES
				OF ALUMINUM & CARBON - INSTALLED NEW
				KELLEY AEROSPACE ES48103 OIL FILTER, TO REQUEST
				SAFETED. SERV. ENG WITH 8 QTS AEROSHELL 80C 40W
				PAGE 6 BY Charles H. Mowbray AD 1334075

YEAR: 2005 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
3-26	227.76		3898.2	REMOVED S/P BORE SCORED ALL CYL'S, CLEARED
Continued	195.1			S/P & REINSTALLED USING NEW S/P CASSETS -
				TORQUED TO 360"LB'S - LEADS REINSTALLED.
				Charles H. Snow AP 1334075.
3/26			3898.2	PROP. REMOVED AND SENT TO HEARTLAND
S/O/A	1368.6			AIRCRAFT FOR C.H.
				Charles H. Snow AP 1334075.
3/26			3898.2	INSTALLED NEW ALT BELT PN 51597-1-
				37.5 Charles H. Snow AP 1334075.

PAGE 7

YEAR: 2005 DATE	RECORDING TACH TIME	ITEM: 12 944531 PN: S1597-1-37.5 U/M: EA DESC: BELT V QTY: 1	1. Approving National Aviation Authority/Country: FAA/UNITED STATES	2. AUTHORIZED RELEASE CERTIFICATE FAA FORM 8130-3, AIRWORTHINESS APPROVAL TAG	3. Form Tracking Number: 944531	4. ORGANIZATION Cessna Aircraft Company Cessna Parts Distribution Dept. 702 5800 E Pawnee, Wichita, KS 67218	5. Work Order/Contract/Invoice Number: 490844	6. Item: 12	7. Description: BELT V	8. Part Number: S1597-1-37.5	9. Eligibility: * 152	10. Quantity: 1	11. Serial/Batch Number: 2Q04	12. Status/Work: New	13. Remarks: AIRWORTHINESS APPROVAL - PARTS. THIS FORM IS NOT AN EXPORT APPROVAL. 152,172,172RG,177,177RG,182,210,421,R182 PO# 02372	14. Certifies the items identified above were manufactured in conformity to: ☒ Approved design data and are in a condition for safe operation. ☐ Non-approved design data specified in Block 13.	15. ☒ 14 CFR 43.3 Return to Service ☐ Other regulation specified in block 13	16. Approval/Authorization No.: 100129CE	17. Name (Typed or Printed): KENNETH E. WYSOCKI SR., ODARF	18. Date (m/d/y): 03/10/2005	19. Authorized Signature:	20. Approval/Certificate No.:	21. Technician or Repair Facility: CYL'S, CLEARED CASSETS - STAINED. 75. HEARTLAND 75. PN 51597-1- 4075.
3-26	22	944531	FAA/UNITED STATES	AUTHORIZED RELEASE CERTIFICATE FAA FORM 8130-3, AIRWORTHINESS APPROVAL TAG	944531	Cessna Aircraft Company Cessna Parts Distribution Dept. 702 5800 E Pawnee, Wichita, KS 67218	490844	12	BELT V	S1597-1-37.5	152	1	2Q04	New	AIRWORTHINESS APPROVAL - PARTS. THIS FORM IS NOT AN EXPORT APPROVAL. 152,172,172RG,177,177RG,182,210,421,R182 PO# 02372	☒ Approved design data and are in a condition for safe operation. ☐ Non-approved design data specified in Block 13.	☒ 14 CFR 43.3 Return to Service ☐ Other regulation specified in block 13	100129CE	KENNETH E. WYSOCKI SR., ODARF	03/10/2005			CYL'S, CLEARED CASSETS - STAINED. 75. HEARTLAND 75. PN 51597-1- 4075.

PAGE 7

[illegible][illegible]

YEAR: 2005 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
12/3	3759.8		3940.3	ENGINE ANNUAL INSPECTION COMPRESSION CHECK ENG. WARM CYL #1 - 80/8 #2 - 80/8 #3 - 80/7 #4 - 80/8 MAGNETO'S TIMING ADJUSTED TO 25° BTDC CLEANED ALL SPARK PLUGS, CHK'd GAP, BOMB TESTED & REINSTALLED TORQUED TO 360" LB'S. CHK'd ENG. CONTROLS FOR TRAVEL & SECURITY LUBI. CONTROLS. ADJUSTED ALT. BELT TENSION TIGHTEN & SAFETIED ADJ. BOLT. CONTINUE NEXT PAGE

YEAR: 2005 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
12/3	3759.8		3940.3	ALL ACCESSORIES CHK'd FOR SECURITY & LEAKS ALL ENG. HOSES CHK'd FOR SERVICEABILITY & SECURITY REPL. 3 EA. ENG ^{CH} DOWN COWL MOUNTS. INSTALLED MISSING LANDING WIFE TERMINAL SCREW. WASHED ENG. CHK'd FOR LEAKS ON RUN UP NONE NOTED - CHK'd BATT. BUS VOLTAGE HIGH 16V - REMOVED REGULATOR & CLEANED TERMINALS - REINSTALLED & BATT. VOLTAGE CHECKS 13.8-14 VOLTS ON RUN-UP. SAIB-PROP.GOV. 1040 SPACER - N/A GOV. INST. 1992 AD 2005-19-11 N/A ENG. O.H. 1992 AD 2004-10-14 N/A NO PROP STRIKE CONT. NEXT PG

[illegible]

YEAR: 2006 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
1-2				AD 2005-26-10 N/A EEXLYI'S NOT INSTALLED. - Charles H. Morris AP 1334075.
3-7				
3-7				AD 2006-03-08 AERO ADVANTAGE VACUUM PUMP NOT INSTALLED THIS ENGINE * Charles H. Morris AP 1334075

YEAR: 2006 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
3-7	0:00 5:04			
3-7	3940.5	3968.5		REMOVED MCCAULEY PROP. GOV. PIN C290-D3D/T11, SN 71856 AND ROUTED TO TUFFIN AIRE INC. FOR O/H. Charles H. Snow A/P 1334075.
3-7	0:00	T S O/H		INSTALLED MCCAULEY PROP. GOV. PIN C290D2-J/T11, S/N 730490 TORQUED MOUNT BOLTS TO 110" LBS & SAFETIED WIRES. ENG. GROUND RUN PROP. CYCLED & RPM CONTROL- LED @ 2700 RPM ON GROUND RUN ANY CONTINUED NEXT PAGE →

1. Approving National Aviation
Authority/Country
FAA/United States

AUTHORIZED RELEASE CERTIFICATE
FAA Form 8130-3, AIRWORTHINESS APPROVAL TAG

3. Form Tracking Number:

6145

4. Organization Name and Address:
Tiffin Aire, Inc.
1778 West U.S. 224
Tiffin, Ohio 44883

5. Work Order/Contract/Invoice
Number:

W.O.6145

6. Item:	7. Description:	8. Part Number:	9. Eligibility:	10. Quantity:	11. Serial/Batch Number:	12. Status/Work:
1	MCCAULEY PROPELLER GOVERNOR	C290D2J/T11	N/A	1	730490	OVERHAULED

13. Remarks:
OVERHAULED IN ACCORDANCE WITH MCCAULEY SERVICE MANUAL 780401 REV.8 12/15/02.
COMPLIED WITH SERVICE BULLETIN:137AA.
COMPLIED WITH SERVICE LETTERS:2000-10B,2001-1F,2003-5,2005-01.

14. Certifies the items identified above were manufactured in conformity to:

- ☐ Approved design data and are in a condition for safe operation.
☐ Non-approved design data specified in Block 13.

19.

☒ 14 CFR 43.9 Return to Service

☐ Other regulation specified in Block 13

Certifies that unless otherwise specified in Block 13, the work identified in Block 12 and described in Block 13 was accomplished in accordance with Title 14, Code of Federal Regulations, part 43 and in respect to that work, the items are approved for return to service.

15. Authorized Signature:

16. Approval/Authorization No.:

20. Authorized Signature:

21. Approval/Certificate No.:

DTXR341D

17. Name (typed or Printed):

18. Date (m/d/y):

22. Name (Typed or Printed):

Gary E. Bibler

23. Date (m/d/y):

MAR.01,2006

User/Installer Responsibilities

It is important to understand that the existence of this document alone does not automatically constitute authority to install the part / component / assembly.
Where the user/installer performs work in accordance with the national regulations of an Airworthiness Authority different than the airworthiness authority of the country specified in block 1, it is essential that the user/installer ensures that his/her airworthiness authority accepts parts/components/assemblies from the airworthiness authority of the country specified in block 1. Statements in block 14 and 19 do not constitute installation certification. In all cases, aircraft maintenance records must contain an installation certification issued in accordance with the national regulations by the user/installer before the aircraft may be flown.

FAA FORM 8130-3 (6-01) *Installer must cross-check eligibility with applicable technical data.

MSN: 0052-00-012-9005

YEAR: 2006 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
3-7				PROP. GOV. CHECKED FOR OIL LEAKS NONE NOTED. REF: 8130-3 ATTACHED INVOICE #6145 ON FILE Charles H. Morris AP 1334075
3-7				NEW REPLACED PROP. GOV. CONTROL ASSY - WITH MCFARLANE MCL299506-0105 SECURED @ ALL MOUNT POINTS - ROD END ADJUSTED & LAN NUT TIGHTEN - ROD END BOLT NUT TIGHTEN & CUTTER PIN INSTALLED - TOTAL TRACEL CK - OK Charles H. Morris AP 1334075.

YEAR: 2006 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
6/4	3785.6		3984.9	DRAINED OIL & REMOVED FILTER INSTALLED 7 QTS AERO SHELL ROTAX 90W OIL & CM 48103-1 OIL FILTER - SAFETY FILTER. Charles H. Morris AP 1334075.
6/4	3785.6			INSTALLED 8 EA NEW AUTO/ITE UREA 38E SPARKPLUGS. Charles H. Morris AP 1334075.

FAA Form 8130-3, AIRWORTHINESS APPROVAL TAG

AUTHORIZED RELEASE CERTIFICATE

FAA Form 8130-3, AIRWORTHINESS APPROVAL TAG

1. Approving National Aviation Authority/Country FAA/UNITED STATES		2. Form Tracking Number: 06.29.06.12.12.00	
4. Organization Name and Address: LAMAR TECHNOLOGIES LLC 14900 40 TH AVE. N.E. MARYSVILLE, WASHINGTON 98271		5. Work Order/Contract/Invoice Number: W/O #: 481A	

6. Item:	7. Description:	8. Part Number:	9. Eligibility:	10. Quantity:	11. Serial/Batch Number:	12. Status/Work:
1	12V STARTER	31A22206 PM1201	LYCOMING 320,360,540 SERIES	1 ea.	85027012	"REBUILT"

13. Remarks*
 ABOVE ITEM REBUILT AND TESTED PER LAMAR TECHNOLOGIES SPECIFICATIONS DWG # PM1201—H REV G 03/24/2006
 AND PER THE REQUIREMENTS OF 14 CFR 43.3 (J)
 ALL APPLICABLE SERVICE BULLETINS AND A.D. NOTES COMPLIED WITH TO DATE.
 COMPLETE DETAILS HELD ON FILE W/O # 481A
 PRESERVED FOR SHORT TERM STORAGE.

14. Certifies the item identified above were manufactured in conformity to: ☐ Approved design data and are in condition for safe operation. ☐ Nonapproved design data specified in Block 13.		19. ☒ 14 CFR 43.9 Return to Service ☐ Other regulation specified in Block 13 Certifies that unless otherwise specified in block 13, the work identified in Block 12 and described in Block 13 was accomplished in accordance with Title 14, Code of Federal Regulations, part 43 and in respect to that work, the items are approved for return to service.	
16. Authorized Signature:	16. Approval/Authorization No.:	20. Authorized Signature:	21. Approval/Certificate No.:
17. Name (Typed or Printed):	18. Date:	22. Name (Typed or Printed):	23. Date:
		ALLAN T SALDECKI	Jun/29/2006

User/Installer Responsibilities
 It is important to understand that the existence of this document alone does not automatically constitute authority to install the part/component/assembly.
 Where the user/installer performs work in accordance with the national regulations of an airworthiness authority different than the authority of the country specified in Block 1, it is essential that the user/installer ensures that his/her airworthiness accepts parts/components/assemblies from the airworthiness authority of the country specified in Block 1.
 Statements in Block 14 and 19 do not constitute installation certification. In all cases, aircraft maintenance records must contain an installation certification issued in accordance with the National regulations by the user/installer before the aircraft may be flown.

10-4				REMOVED PRESTOLITE MZ-4206 STARTER INOP.
				INSTALLED REBUILT LAMAR STARTER 31A22206 PN - PM-1201 SN 8502712 FORM 8130-3 ATTACHED THIS PAGE.
				COMPUTED NEW CG.
				Charles H. <u>Downey</u> A#P 1334075 -
10-4				
10-4				REPLACED CARB. AIR FILTER ELEMENT PN - BA-5705.
				Charles H. <u>Downey</u> A#P 1334075 -

YEAR: 2000 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
11-15-20	3824.9		4024.2	TSMOHT 1494.6 MILLIONUMPH'S 498.1 ENGINE INSP. 100HR PERFORMED PER CESSNA MAINT. MANUAL INSP. GUIDE 1. PERFORMED COMPRESSION CHECK #1 CYL - 80/78 #2 80/79 #3 80/79 #4 80/79. CHECKED MAG. TIMING 25° BTDC, CLEANED ALL SP & REINSTALLED TORQUES TO 360" LBS. DRAINED ENG. OIL, OPENED OLD OIL FILTER & VISUAL INSP. NOTHING NOTED IN FILTER. SERVICED WITH 8 QTS ARMO SAE 15W50 OIL. & MAG CH 48103-1 OIL FILTER INSTALLED, & TORQUED & SAFETYED. 2. REMOVED ENG. MUFFLER SARDON & VISUAL INSP. FOR CRACKS & DEFORMALITES. CK - NORMAL. CONTINUED NEXT PAGE

1. Approving National Aviation
Authority/County

FAA/United States

AUTHORIZED RELEASE CERTIFICATE

FAA Form 8130-3, AIRWORTHINESS APPROVAL TAG

3. Form Tracking Number:

6340

5. Work Order/Contract/Invoice
Number:

W/O 6340

4. Organization Name and Address:

Tiffin Air, Inc.
1778 West U.S. 224
Tiffin, Ohio 44883
FAA Certified Repair Station No.
DTXR341D

6. Item:

7. Description:

1 WOODWARD ROPELLER GOVERNOR

8. Part Number:

B210480

9. Eligibility:

N/A

10. Quantity:

1

11. Serial/Batch Number:

1758081

12. Status/Work:

OVERHAULED

13. Remarks:

OVERHAULED IN ACCORDANCE WITH WOODWARD SERVICE MANUAL 330028 1987.
COMPLIED WITH SERVICE BULLETINS 33531, 33571.

14. Certifies the items identified above were manufactured in conformity to:

- ☐ Approved design data and are in a condition for safe operation.
☐ Non-approved design data specified in Block 13.

15. Authorized Signature:

16. Approval/Authorization No.:

20. Authorized Signature:

17. Name (Typed or Printed):

18. Date (month):

22. Name (Typed or Printed):

Gay E. Bibler

21. Approval/Certificate No.:

DTXR341D

23. Date (month):

FEB/01/2007

User/Installer Responsibilities

It is important to understand that the existence of this document alone does not automatically constitute authority to install the part / component / assembly. While the user/installer of the part / component / assembly is responsible for ensuring that the part / component / assembly is installed in accordance with the applicable regulations of the country specified in block 1, statements in block 14 and 15 do not constitute installation certification. In all cases, aircraft maintenance records must contain an installation certification issued in accordance with the national regulations by the user/installer before the aircraft may be flown.

FAA FORM 8130-3 (6-01) *Installer must cross-check eligibility with applicable technical data.

MSN: 0052-00-012-9005

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
2-19-07	3838.7	on file	682	REMOVED M ^C AGLEY PROP. GOV. DUE SER RPL SURGE - SN 730490 PN C290D2-J/T11. Charles H. Morris AEP 1334075
2-19-07	3838.7	on file	682	INSTALLED WOODWARD GOV. M/N B210.490 S/N 1758080 O.H BY TIEKIN AIRC, REF; INVOICE # 6340 DATED 2/9/2007 ON FILE. GOV. INSTALLED PER .STC SA300CE INSTALLATION INSTRUCTIONS 9963-056 DATED APRIL, 12, 1974 Charles H. Morris AEP 1334075
		1.0		Test Flow N TO. Settings & operation NORMAL 7400 RPM Charles H. Morris (Pick up # 142-5671)

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
5-16	3867.8			OIL DRAINED & OIL FILTER REMOVED & C/O TOP & EXAMINED FOR METAL CUT. NONE NOTED - INSTALLED NEW Champion CK #8103-1 OIL FILTER TORQUED & SAFETY. INSTALLED 7 QTS ARD SAEL AW 40 OIL. - CLEARED & ROTATED SPARK PLUGS. RUN 10 & CKD FOR OIL LEAKS, NONE NOTED Charles H. Morris AEP 1334075 END

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
9-15	3904.3			OIL DRAINED, OIL FILTER REMOVED CUT-OPEN & EXAMINED NO METAL OR OTHER CONTAMINANTS NOTED - SERVICED WITH 7 QTS AERO-SHELL 15W50 OIL & NEW CH 48103-1 FILTER INSTALLED TORQUED 16 FT. LBS & SAFETY WIRED - CLEANED ALL SP, PERFORMED COMPRESSION CK - #1-80/75 #2-80/75 #3-80/78 #4-80/75, CHECKED & RESET TIMING TO 25° BTDC, ROD-UP BNG. NO OIL LEAKS NOTED MAG. DROP NORMAL. Charles A. Dorman AEP 1334075

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspection Entries must be and Facility
9-15	3904.3			FAA FORM 8130-3 AIRWORTHINESS APPROVAL TAG U.S. DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION UNITED STATES 4. ORGANIZATION CESSNA AIRCRAFT COMPANY CESSNA PARTS DISTRIBUTION 5800 E. PAWNEE, WICHITA, KS 67218 6. ITEM 0009 7. DESCRIPTION FILTER OIL 8. PART NUMBER CH48103 9. ELIGIBILITY TBV BY INSTALLER FAA/PMA 10. QTY. 1 11. SERIAL/BATCH NO. N/A 12. STATUS/WORK NEW 047714 00073363
SPARK PLUGS REINSTALLED & TORQUE TO 360" LB				
WORTHINESS APPROVAL-PARTS. THIS FORM IS NOT AN EXPORT APPROVAL PARTS MUST BE ACCOMPANIED BY MAINTENANCE HISTORY INCLUDING TOTAL TIME/TOTAL CYCLES/TIME SINCE NEW. 18. DATE 07/06/00 19. Return to Service in Accordance with FAR 43.9 Certifies that the work specified in block 13 (or attached) was carried out in accordance with FAA airworthiness regulations and in respect to the work performed the part(s) is (are) approved for return to service. 20. AUTHORIZED SIGNATURE Wm Lips PC4 21. CERTIFICATE NO. 1334075 22. NAME (TYPED OR PRINTED) Wm Lips 23. DATE 07/06/00 24. (OPTIONAL) INSTALLER MUST CROSS CHECK ELIGIBILITY WITH APPLICABLE TECHNICAL DATA.				

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN	Description of Inspection
9-15	3904.3			1. Form Tracking Number: 1422271 2. AUTHORIZED RELEASE CERTIFICATE FAA FORM 8130-3, AIRWORTHINESS APPROVAL 3. Work Order/Contract/Invoice Number: 670808 4. Item: 6 MOUNT 5. Part Number: S1115-29 6. Eligibility: 150 7. Quantity: 1 8. Batch Number: 3Q06 9. Status/Work: New 10. Remarks: AIRWORTHINESS APPROVAL - PARTS. THIS FORM IS NOT AN EXPORT APPROVAL. 11. PO# 06-11751 12. Certifies the items identified above were manufactured in conformity to: ☒ Approved design data and are in a condition for safe operation. ☐ Non-approved design data specified in Block 13. 13. Certifies that unless otherwise specified in Block 13, the work identified in Block 12 and described in Block 13 was accomplished in accordance with Title 14, Code of Federal Regulations, part 43 and in respect to that work, the items are approved for return to service. 14. 14 CFR 43.9 Return to Service ☐ Other regulation specified in block 13 15. Authorized Signature: James A. Schild 16. Approval/Authorization No.: 100129CE 17. Name (Typed or Printed): JAMES A. SCHILD, ODARF 18. Date (m/d/y): NOV/20/2006 19. 20. Authorized Signature: [Blank] 21. Approval/Certificate No.: [Blank] 22. Name (Typed or Printed): [Blank] 23. Date (m/d/y): [Blank] 24. User/Installer Responsibilities It is important to understand that the existence of this document alone does not automatically constitute authority to install the part/component/assembly. Where the user/installer performs work in accordance with the national regulations of an airworthiness authority different than the airworthiness authority of the country specified in Block 1, it is essential that the user/installer ensures that his/her airworthiness authority accepts parts/components/assemblies from the airworthiness authority of the country specified in Block 1. Statements in Blocks 14 and 19 do not constitute installation certification. In all cases, aircraft maintenance records must contain an installation certification issued in accordance with the national regulations by the user/installer before the aircraft may be flown. 25. FAA Form 8130-3 (6-01) *Installer must cross-check eligibility

ITEM: 6
PN: S1115-29
ORDER: 1422271
DESC: MOUNT
QTY: 1
U/M: EA

5 PARK PI
REINSTALLED
TURNS

1422271
6

an or Repair
MOVED
ALOR
OLL
3-1 Fil
SABO
FORMS
75
NO
MAL
75

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations
9-13	3911.3			REMOVED RT. SLICK MAG PN. 4370, SN. 00110341 AND ROUTED TO TELEDYNE MATTITUCK SERVICES, INC. FOR 500 HR. INSPECTION. REMOVED LT. SLICK MAG PN. 4373, SN. 001004163 AND ROUTED TO TELEDYNE MATTITUCK SERVICES INC. FOR 500 HR. INSPECTION. Charles H. O'Hanrahan AEP 1334075. - END -

YEAR: <u>2007</u>	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME	ITEM: 4 ORDER: 1851367 PN: CH48103-1 U/M: EA DESC: FILTER OIL QTY: 1	1. Approving National Aviation Authority/Country: FAA/UNITED STATES	2. AUTHORIZED RELEASE CERTIFICATE FAA FORM 8130-3, AIRWORTHINESS APPROVAL TAG	3. Form Tracking Number: 1851367
DATE <u>9-13</u>	<u>3911.3</u>				4. Organization Name and Address: Cessna Aircraft Company Cessna Parts Distribution Dept. 702 5800 E Pawnee, Wichita, KS 67218	5. Work Order/Contract/Invoice Number: 785518	
					6. Item: 4	7. Description: FILTER OIL	8. Part Number: CH48103-1
					9. Eligible: N/A	10. Quantity: 1	11. Serial/Batch Number: N/A
					12. Status/Work: New		
13. Remarks: AIRWORTHINESS APPROVAL - PARTS. THIS FORM IS NOT AN EXPORT APPROVAL.							
PO# POA07-14092							
14. Certifies the items identified above were manufactured in conformity to: ☒ Approved design data and are in a condition for safe operation. ☐ Non-approved design data specified in Block 13.							
15. Authorized Signature: <i>Kenneth E. Wysocki</i>							
16. Approval/Authorization No.: 100129CE							
17. Name (Typed or Printed): KENNETH E. WYSOCKI SR., ODARE							
18. Date (m/d/y): DEC/18/2007							
19. ☐ 14 CFR 43.9 Return to Service ☐ Other regulation specified in block 13 Certifies that unless otherwise specified in Block 13, the work identified in Block 12 was accomplished in accordance with Table 14, Code of Federal Regulations, part 43 and in respect to that work, the items are approved for return to service.							
20. Authorized Signature:							
21. Approval/Certificate No.:							
22. Name (Typed or Printed):							
23. Date (m/d/y):							
User/Installer Responsibilities It is important to understand that the existence of this document alone does not automatically constitute authority to install the part/component/assembly. Where the user/installer performs work in accordance with the national regulations of an airworthiness authority different than the airworthiness authority of the country specified in Block 1, it is essential that the user/installer ensures that his/her airworthiness authority accepts parts/components/assemblies from the airworthiness authority of the country specified in Block 1. Statements in Blocks 14 and 19 do not constitute installation certification. In all cases, aircraft maintenance records must contain an installation certification issued in accordance with the national regulations by the user/installer before the aircraft may be flown.							
FAA Form 8130-3 (6-01) *Installer must cross-check eligibility with applicable technical data. NSN: 0052-00-01							

RT.MAG

WORK ORDER

Work Order No. 41806 Customer CHARLES H. MORRIS

Part No. 4370 Serial No. 00110341

Nomenclature 4300 SERIES SLICK MAGNETO

Description of work performed 500 Hrs INSPECTION; REPLACED POINTS AND BRUSH; BENCH TESTED - OK

All work performed in accordance with applicable manufacturer's maintenance and parts manuals.

Date 10/09/07 Signed [Signature]

TELEDYNE MATTITUCK SERVICES, INC. FAA Repair Station T10R507Y

YEAR: 2007	WORK ORDER	
Work Order No. <u>61806</u>	Customer <u>CHARLES H. MORRIS</u>	
Part No. <u>4373</u>	Serial No. <u>00100463</u>	
Nomenclature <u>4300 SERIES SLICK MAGNETO</u>		
Description of work performed <u>500 Hr INSPECTION; REPLACED POINTS AND BRUSH; BENCH TESTED - OK</u>		
All work performed in accordance with applicable manufacturer's maintenance and parts manuals.		
Date <u>10/09/07</u>	Signed <u>Jim C. Boyle</u>	
TELEDYNE MATTITUCK SERVICES, INC.		FAA Repair Station T10R507Y

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
10-13	3911.3		3911.3 A	REINSTALLED SLICK MAGNETOS FOLLOWING 500 HR. INSPECTION - USING NEW PLAUROTAX SERIES MAGS TIMED & SYNCH'D. AT 25° BTC MOUNT NUTS TORQUED TO 14' LBS.
				(NOTE:) MAG'S POULLED EARLY BECAUSE ENG. HARD TO START & EXCESSIVE MAG. DROP.
				R.T. MAG. PN. 4370 SN. 00110341.
				L.T. MAG. PN. 4373 SN. 00100463.
				ENGINE RUN & CK'D FOR OIL LEAKS, & MAG. DROP 75R, 75L, ENG. COOLING
				REINSTALLED. SEE YELLOW TAGS ATTACHED THIS LOG BOOK. WIO. & INVOICE ON FILE.
				WIO. #61806, INVOICE #41434, DATED 10-9-07
				Charles H. Morris: ASP 1334075.

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
11-23	3922.7		4122.0	TSMolt 1592.4 ENG. INSP. ACCORDING TO 100HR INSPECTION - REPAIRED CRACKED BARREL #2 CYL. REPL. SCAT-TUBING CARB. INLET & OIL COOLER. INSTALLED NEW CARB. INLET. FILTER. INSTALLED NEW SHAFT IN CARB AIR CONTROL BOX. WASHED ENG. Charly H. Dorman AP 1334075 — End —

YEAR: 2007 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
11-23	3922.7	TT 4122.0	TSMolt 1592.4	I certify that this <u>Engine</u> has been Inspected in accordance with a <u>Annual</u> Inspection, and was determined to be in an Airworthy condition. Date <u>23 Nov 07</u> (Tach or TT <u>3922.7</u> Raymond A. Rakers 18326021A
3-22-08	3950.7			CHANGED ENG. OIL & OIL FILTER INSTALLED 7 Q'S ALCOHOL 15W 50 INSTALLED NEW CH #8103-1 OIL FILTER TORQUED 14' LBS & SAFETY WIRED - PDE RUN CIC FOR OIL LEAKS. NONE NOTED - Charly H. Dorman AP 1334075

[illegible]


YEAR: 2008	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
DATE 26 Dec	402206		42219 42219	ENGINE 100 HR INSPECTION
			ITEM	#1. PERFORMED COMPRESSION CHECK (ENG. COLD.) CYL #1 $\frac{80}{75}$ CYL #3. $\frac{80}{75}$, CYL #2. $\frac{80}{75}$ CYL #4. $\frac{80}{75}$.
			ITEM	#2. REMOVED ALL SPARK PLUGS CLEANED, RECAPPED 1022 & BOMB CK'D ALL REINSTALLED USING NEW COPPER GASKETS TORQUED TO 360" LB'S.
			ITEM	#3. MAGNETO TIMING CHECKED & SET TO 25° BTDC.
			ITEM	#4. MANIFOLD PRESSURE SENCE LINE & UNION @ #3 CYL CLEANED OUT.
			ITEM	#5. REPL. TACH'S #4 CYL HEATER PROBE P/N TAS-100

CONTINUED NEXT PAGE →

YEAR: 2008 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
26 Dec	4022.6		4221.9	100 HR INSP. #6. FIREWALL FUEL STRAINER DISABLED & INSP. & CLEANED, REASSEMBLED USING NEW O-RINGS - TORQUED BOWL NOT TO 30" LBS & SAFETY WIRE'D. PRESSURE CHECKED FOR LEAKS.
				ITEM #7 ENG. COOL LOWER LEFT BRACKET BROKEN; LOWER ATTACHMENT REPLACED.
				ITEM #8 EXHAUST MUFFLER & PIPES INSP. FOR CRACKS, SECURITY.
				ITEM #9, ALL ACCESSORIES INSP. FOR SECURITY.
				ALL ENG. SERVICE HOSE INSP. FOR CONDITION & SECURITY. & ENG. CONTROLS CK'D FOR SECURITY & TRAVEL
				ITEM #10. TOP & BOTTOM ENG. COOL NOSE INLET PAINT TOUCH-UP.

Items #6 thru #10
checked H-7 MONDAY
APR 1384075

— END —

YEAR: 2008 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
26 Dec	4022.6		4221.9	
			TSMCH 1692.3	
				I certify that this <u>ENGINE</u> has been Inspected in accordance with a <u>ANNUAL</u> Inspection, and was determined to be in an Airworthy condition.
				Date <u>26 Dec 08</u> Tach or <u>TT</u> <u>4022.6</u>
				Raymond A. Rakers 18826021A
				

Time Since New
Superior cyl = 695.8

YEAR: DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
4-11	4044.9			DRAINED ENGINE OIL, REMOVED OIL FILTER - PUT OVEN FILTER & INSP. SENT OIL SAMPLE TO BLACKSTONE LAB. - SAMPLE OK NORMAL - INSTALLED FILTER NEW AIR TEMPEST AA48103 TORQUED TO 14 LBS & SAFETY, CLOSED OIL DRAIN & SERVICED WITH 7 QTS AERO SABL 15W-50. A & P Charles H. Mowbray AP 1334075r — END —

YEAR: DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
9-28	4082.8			DRAINED ENG. OIL & REMOVED FILTER, INSTALLED 7 QTS AERO SABL 100 GRADE 50 WT. INSTALLED NEW TEMPEST AA48103 OIL FILTER TORQUED 14 LBS & SAFETY PERFORMED COMPRESSION C/K ENG WARM #1 CYL 80/78 #2 CYL 80/77 #3 CYL 80/77 #4 CYL 80/70. INSTALLED 8 EA NEW AUTO LITE UREA 38E SPARK PLUGS TORQUED TO 360" LBS. WASH CLEANED ENG. - RUN-UP OK FOR OIL LEAKS - ADJUSTED 1 OLE MIX & SPEED. CHECKED MAG TIMING 25° BTDC DID NOT NEED ADJUSTING. Charles H. Mowbray AP 1334075r

41 80/78 #3 80/77
#2 80/77 #4 80/70
TACH 4082.8 9-27-09

YEAR: DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
3/11/10	4091.6		420.9	Reinstalled This ENGINE O-360 ^{AIFB} FLAC ^{9/11} — L-15677-26A After Overhaul, with New Barry Mount Kits P/N-94011-20, Bolts and nuts. New IGN Harness installed P/N M4005, Oil Cooler Reinstalled After overhaul by Pacific Oil Cooler Service P/N 8406E-SV; Overhauled Magnitos Per union master manual. Installed new UREMS30E S/plugs, New induction filter installed P/N BAST05. Replaced FLOW. Charging hose with New. Engine Overhaul OK! Leak OK normal. Engine serviced with 50 wt Mineral Oil For ENG (Cont.)

YEAR: DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
				Break in. ENG has been ground run. Per by engine Overhaul man. Procedures. ENG is approved For Return to Service for work performed. Levi Roscorans AP1613512


YEAR: 2011 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
	4364.5			
				DRAINED ENGINE OIL & REMOVED
				OIL FILTER -
				INSTALLED 7 QTs 15W 50 AERO SHELL
				OIL & KELLEY ES 48104 OIL FILTER, TORQUED
				15' LBS & SAFETY W, RD.
				PERFORMED COMPRESSION CK. #1 ⁸⁰ / ₇₅ #2 ⁸⁰ / ₇₈ #3 ⁸⁰ / ₇₄ #4 ⁸⁰ / ₇₃
				ENG. WARM.
				CK. & ADJUSTED MAG. TIMING TO 25° BTC.
				S/P CLEANED, REINSTALLED TORQUED TO 360' LBS.
				CK'D ALL ENG. CONTROLS FOR TRAVEL & SECURITY.
				Charles H. Morris AP 1334075.

YEAR: DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
				N34125 TACH-4165.2 3/22/2011
				ENGINE: LYCOMING O-360-A1F6 S/N-L-15677-36A SMOH-73.6 T.T.-4364.5
				COMPLETED AN ANNUAL INSPECTION IN ACCORDANCE WITH CESSNA SERVICE
				MANUAL CHECKLIST AND FAR 43 (d). COMPRESSIONS ARE #1, 74 #2, 76 #3, 72 #4, 73 ' ALL
				OVER 80. MAG TIMING CHECKED. LEAK AND OPERATIONAL CHECKED NORMAL
				AD'S CHECKED THRU THIS DATE.
				I CERTIFY THIS ENGINE HAS BEEN INSPECTED IN ACCORDANCE WITH AN ANNUAL
				INSPECTION AND IS IN AIRWORTHY CONDITION.
				 LEVI ROSECRANS AP1613512IA

YEAR: 2012 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
5/4/12	4196.5			inspected this engine in accordance with Cessna Service Manual CK List Ann FAR 43. Compressions are as follows #1, 76, #2, 76, #3, 76 #4, 75. All over 20. I Certify this engine has been inspected in accordance with an annual inspection and is in Airworthy Condition. AD's OK'd this date Leif Hansen AP 1613512 IA.

YEAR: 2012 DATE	RECORDING TACH TIME	TODAY'S FLIGHT	TOTAL TIME IN SERVICE	Description of Inspections, Tests, Repairs and Alterations Entries must be endorsed with Name, Rating and Certificate Number of Technician or Repair Facility. (See back pages for other specific entries.)
5/11/12	4199.9			REMOVED LAMAR STARTER P/N PM1201 INSTALLED PMA NO. PQ0852SW P/N 149-NL SIN FN-0312101 SKY - TEC STARTER. 11 MAY 2012. Computer NEW CG. AEP 1334075 Charles H. Morvill
5/11/12	4199.9			ENG. OIL DRAINED & 7 QTs AEROSHELL 80W-40W INSTALLED. OIL FILTER REMOVED & NEW ES48104 KELLOY OIL FILTER INSTALLED. TORQUED 16 LBS & SAFTED. Charles H. Morvill AP 1334075 - One -

YEAR: 2015 DATE	TOTAL TIME IN SERVICE	Reference of Major Repairs and Major Alterations To FAA Form 337 by Date, or to the Work Order by Number and the Approving Agency
4/18	4298.5	100% Insp. Compressed CK 1 80/2 80/2 80/2 80/2 DRAINED OIL & REMOVED FILTER, INSTALLED NEW TEMPEST AA 48103-2 OIL FILTER TORQUED TO 14' TORQUE SAFETY WRENCH REPL. TWO RIPPED RIVETS @ 11 O'CLOCK POSITION FIREWALL COWLING MOUNT BRACKET. REPL. OUTRD LEG OF COW- LING MOUNT BRACKET @ 3 O'CLOCK POSITION BW FIREWALL. CHECK FOR OIL & FUEL LEAKS, CONTROLS CK FOR FULL TRAVEL & SECURITY, REINSTALLED COWLING & SECURED. REPL. INSTALLED 7 QTS AERO SWOL 100 PLUS OIL. Charly H. Brown A P 1334075 Z

YEAR: 2015 DATE	TOTAL TIME IN SERVICE	Reference of Major Repairs and Major Alterations To FAA Form 337 by Date, or to the Work Order by Number and the Approving Agency
18 APR 2015		NO REPAIR ADS, NO NEW ADS THIS TIME. TACH 4298.5 TSMOUT 206.9 ETT 4497.8
		I certify that this AIRCRAFT has been Inspected in accordance with a <u>ANNUAL</u> Inspection, and was determined to be in an Airworthy condition. Date 18 APR 2015 Tach or <u>4298.5</u> Raymond A. Rakers 18326021A 

Notes

